


# GP Batteries

## Product Specification

Model no.: GPPB410



Unit : mm

Product Name	: GP PowerBank GPPB410
Description	: Continuous NiMH Battery Charger (Plug-in Type)
Input Voltage	: 230V AC 50Hz (GS/BS) 120V AC 60Hz (US)
Input Power	: 6W Max.
Application	: For charging 1 or 2 pcs AA / AAA NiMH batteries ; 1 battery per one channel
Output Voltage	: 1.4V DC
Charging Current	: AA     180mA +/- 10%
Output Current	: AAA    180mA +/- 10%
Charging Time	:

Battery Type / Size	Capacity (series / mAh)	Charging Time (hours)
NiMH AA	2100 series ~ 2700 series (min. 2000mAh) ~ (min. 2500mAh)	13.0 ~ 16.0
	1000 series ~ 1800 series (min. 1000mAh) ~ (min. 1800mAh)	6.5 ~ 11.5
NiMH AAA	600 series ~ 1000 series (min. 600mAh) ~ (min. 930mAh)	4.0 ~ 6.5

# GP Batteries

---

## Product Specification

Model no.: GPPB410

---

MTBF : 30000 hours (at ambient temperature 25°C)  
Operation Temperature : 0°C to 40°C  
Storage Temperature : -20°C to 60°C  
LED Indication : 2 x Amber Color LED for two channels ; two channels operate individually

Condition	LED indicator
Charging in Progress	LED on
Batteries Removed	LED off

Dimension : 108 (L) x 43 (W) x 33.3 (H)mm  
Weight : 119g (approx)  
Approval : PB410GS – GS, CE  
PB410BS – CE  
PB410US – ETL, FCC  
Compliance : RoHS and REACH  
Warranty Period : 12 months from ex-factory date